

SMOKEX CHIMNEY FANS



When a naturally venting chimney or flue is impossible to achieve, the Smokex Chimney Fan is the solution.

The fan is installed as “the terminal” to the chimney with controller etc..., installed, adjacent to the appliance. The Smokex Chimney Fan is suitable for all types of appliances including open fires, gas fires, stoves, cookers and boilers and will guarantee the correct constant draught in the flue way.

- **Vertical discharge**
- **Body made of cast aluminium**
- **Max. smoke temperature of appliance : 250°C - 450°C with dilution bolts**
- **With stainless-steel axial blades or backward curved impellers**

Poujoulat *“designed with you in mind”*

Simple and easy to install on all chimney and flue types



Fan support plate

Fan size selection and technical detail

For a chimney of 7 to 8 m in length our fan selection would be as per the table below

Fan unit size	SMX2	SMX4	SMX6	SMX8
Fireplace opening size (in square meter)	0.2 to 0.45	0.45 to 0.7	0.65 to 1.0	0.4 to 0.9
Flue diameter (in mm)	Ø150 to Ø230	Ø200 to Ø290	Ø250 to Ø320	Ø125 to Ø265
Volts/Amps/Watt	240/0.32/70	240/0.4/90	240/0.6/130	240/0.55/120
Fan speed RPM	1400	1400	1400	1400
Fan weigh in Kg	11.5	14.5	16.5	14.5

